



STANDARD FEATURES

INPUT - 350ohm STRAIN GAUGE
0.8" HIGH 5-DIGIT DISPLAY
LED BAR GRAPHS - Process+Set Value
0-5000psi + 0-10,000psi RANGES
ALARM - High or Low (NO/NC 240V,5A)
POWER - 90-260VAC
1% ACCURACY, MANUAL ZERO
PROCESS VALUE RETRANS - 4-20mA
60" FLEX HOSE, 6pin BAYONET CONNECT.

OPTIONS

RETRANSMISSION OPTIONS :
0-5, 0-10VDC or 0-20mA
POWER - 24V-AC/DC
CONNECTOR - 6pin Screw
8pin Screw

MODEL CODE

MG-IND - P - Scale - PV Retrans - Cable Length - Connector - Power

5M - 5,000psi
10M - 10,000psi
Custom

M - 4-20mA
0 - 0-10mA
1 - 0-20mA
5 - 0-5VDC
6 - 0-6VDC
10 - 0-10VDC

6 - 6ft (2m)
12 - 12ft (3.7m)
25 - 25ft (7.7m)

6B - 6pin Bayonet - 85-265VAC
6S - 6pin Screw **24V** - 24V-AC/DC
8S - 8pin Screw

SPECIFICATIONS - MG-IND

INPUT - PRESSURE TRANSDUCER

350ohm STRAIN GAUGE - 3.33mV/V
EXCITATION VOLTAGE - 10VDC
ACCURACY - 1%

RETRANS of PROCESS VALUE

CURRENT - 4-20mA, 0-10mA, 0-20mA
VOLTAGE - 0-5, 1-5, 0-10VDC

ALARM OUTPUT

Alarms 3A/240VAC resistive.

POWER

Standard 85-265VAC 50/60Hz 10VA
Option 24V AC/DC

ENVIRONMENTAL

Temp&Humid. 10-55degC, 0-95%RH
Insulation 20M ohms min@500VDC
Weight 250-375g