

MHP SERIES TRANSDUCERS



MHP - Transducer

FEATURES MHP

- Standard 3mV/V
- Standard 1/4"-18 NPT Male
- 6pin Bayonet Connector
- 0.5% combined error
- 80% Output Calibration
- 250°F (120°C) Rating
- Ranges from
 - 0-15 to 0-30,000psi
- Wetted Parts
- ALL STAINLESS STEEL

OPTIONS MHP

- OUTPUT OPTIONS
 - 2.5, 3mV/V
- CONNECTOR OPTIONS
 - 4 Pole DIN
- PRESSURE PORT
 - 1/8"-27 NPT Female
 - 1/8"-27 NPT Male

MHP - X

- 3 - 3mV/V
- 2 - 2.5mV/V
- 1
- 1.5
- 3
- 5
- 7.5
- 10
- 15 30
- 20 50

P XX X

- M - Psi x1000
- C - Psi x 100
- B - BAR x100
- P - Psi

X

- S - 6PIN BAYONET
- 4 - 4POLE DIN

X

- S - 1/4"-18 NPT MALE
- 8M - 1/8"-27 NPT MALE
- 8F - 1/8"-27 NPT FEMALE

STOCK LIST - MHP (3mV/V)		
PRESS (psi)	1/8-27NPT (female)	1/4-18NPT (male)
500	✓	✓
1,000	✓	✓
2,500	✓	✓
3,000	✓	✓
5,000	✓	✓
10,000	✓	✓

